

EVA hot melt adhesive film

Specifications :

Price	Contact Us
Brand Name	HengNing
Place of Origin	Shanghai,China
Payment Terms	T/T,L/C,Western Union,etc.
Delivery Detail	10-25 Working Days

Detail Introduction :

EVA hot melt adhesive film is one of the common types of hot melt adhesive film, EVA hot melt adhesive film is made of EVA as the main raw material of hot melt adhesive film products, EVA is a common resin material, its chemical name is ethylene - vinyl acetate copolymer, EVA hot melt adhesive film is commonly colorless transparent or mist.

1. EVA hot melt adhesive film manufacturing method

EVA hot melt adhesive film in accordance with the composition of the hot melt adhesive, EVA as the basic polymer, and then with viscosity enhancers, viscosity modifiers, antioxidants and other additives, made of hot melt adhesive particles. After that, the obtained hot melt adhesive particles are melted and passed through a coating machine or a calender to form a hot melt adhesive film. In EVA hot melt adhesive film, the content of EVA often reaches 60%-90%, so called EVA hot melt adhesive film.

2. EVA hot melt adhesive film by form and use

EVA hot melt adhesive film by form and use

3. EVA hot melt adhesive film used in which areas

EVA hot melt adhesive film is a large amount of hot melt adhesive film in a variety of species, because of its fast curing, low pollution, strong adhesion characteristics, is an environmentally friendly and efficient industrial adhesives. It is widely used in the shoe industry, automotive industry, wallcovering manufacturing and other industries. As EVA hot melt adhesive film has a wide range of bonding, so it has a better bonding to many materials and has an important role in the development of new materials.

类别 Series	材质 Material	型号 Type	宽度 Width (mm)	厚度 Thickness (mm)	熔点 Melting Point (°C)	压烫条件 Press Condition		
						时间 Time (s)	温度 Temp (°C)	压力 Press (Kgf/ m ²)
热 熔 胶 膜 A d h e s i v e F i l m	PA	TA120	15-1650	0.03-0.5	120	10-30	135-140	1.5-3.0
	PES	TES01	15-1650	0.03-0.5	120	10-30	135-140	1.5-3.0
		TES03	15-1650	0.03-0.5	120	10-30	135-140	1.5-3.0
		TES06	15-1650	0.03-0.5	120	10-30	135-140	1.5-3.0
		TES110	15-1650	0.05-0.5	120	10-30	135-140	1.5-3.0
	TPU	TB115	15-1650	0.015-0.5	115	10-30	130-135	1.5-3.0
		TBK115	15-1650	0.03-0.5	115	10-30	130-135	1.5-3.0
		TB95	15-1650	0.05-0.5	95	10-30	110-115	1.5-3.0
		TB65	15-1650	0.015-0.5	65	10-30	80-85	1.5-3.0
		TBE65	15-1650	0.015-0.5	65	10-30	80-85	1.5-3.0
		TBL65	15-1650	0.015-0.5	65	10-30	80-85	1.5-3.0
		TB130	15-1650	0.025-0.5	130	10-30	145-150	1.5-3.0
		EVA	TE70	15-1650	0.015-0.5	70	10-30	85-90
	TE80		15-1650	0.015-0.5	80	10-30	95-100	1.5-3.0
	TEH80		15-1650	0.015-0.5	80	10-30	95-100	1.5-3.0
	TE95		15-1650	0.015-0.5	95	10-30	110-115	1.5-3.0
	TE65		15-1650	0.05-0.5	65	10-30	80-85	1.5-3.0
	TE85		15-1650	0.01-0.5	85	10-30	100-105	1.5-3.0
	PO	TP125	15-1650	0.03-0.5	125	10-30	140-145	1.5-3.0
		TPL100	15-1650	0.05-0.5	100	10-30	115-120	1.5-3.0